NSN 5962-01-276-6460

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-276-6460

Body Length:
Between 0.165 inches and 0.185 inches
Body Outside Diameter:
Between 0.335 inches and 0.370 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
End Application:
Wsd: forrestal class cv; seawolf class ssn; arleigh burke class ddg; supply class aoe; osprey class mhc; ticonderoga class cg (47);
spruance class dd (963); nimitz class cvn; tarawa class lha
Features Provided:
Monolithic
Inclosure Material:
Metal
Inclosure Configuration:
Can
Input Circuit Pattern:
2 input
Criticality Code Justification:
Feat
Design Function And Quantity:
1 amplifier, operational, general purpose
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
36.0 volts power source
Special Features:
Weapon system essential
Terminal Type And Quantity:
8 pin
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A458a0