NSN 5962-01-276-6460

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-276-6460

Body Length:

Between 0.165 inches and 0.185 inches

Body Outside Diameter:

Between 0.335 inches and 0.370 inches

Maximum Power Dissipation Rating:

500.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Wsd: forrestal class cv; seawolf class ssn; arleigh burke class ddg; supply class aoe; osprey class mhc; ticonderoga class cg (47);

spruance class dd (963); nimitz class cvn; tarawa class lha

Features Provided:

Monolithic

Inclosure Material:

Metal

Inclosure Configuration:

Can

Input Circuit Pattern:

2 input

Criticality Code Justification:

Feat

Design Function And Quantity:

1 amplifier, operational, general purpose

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

36.0 volts power source

Special Features:

Weapon system essential

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0