## NSN 5962-01-277-3049

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-277-3049 **Overall Height:** 0.355 inches **Body Length:** Between 0.755 inches and 0.790 inches **Body Width:** Between 0.265 inches and 0.300 inches **Body Height:** Between 0.155 inches and 0.175 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -85.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and programmable and w/enable and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 10 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Memory Device Type:** Rom **Memory Capacity:** Unknown **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life:

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

N/a

## NSN 5962-01-277-3049

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0