

View Online at <https://aerobasegroup.com/nsn/5962-01-277-3338>

**Body Length:**

Between 0.342 inches and 0.358 inches

**Body Width:**

Between 0.342 inches and 0.358 inches

**Body Height:**

Between 0.064 inches and 0.100 inches

**Maximum Power Dissipation Rating:**

36.0 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and low power and schottky and monolithic

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Triple 3 input

**Design Function And Quantity:**

3 gate, and

**Case Outline Source And Designator:**

C-2 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

7.0 volts power source

**Time Rating Per Characteristic:**

25.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

20 leadless

**Specification Data:**

81349-mil-m-38510/310 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0