Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-277-8712

| Body Length:   |  |
|--|--|
| .440 inches  |  |
| Body Width:  |  |
| .285 inches  |  |
| Body Height:   |  |
| .085 inches  |  |
| laximum Power Dissipation Rating:                                    |  |
| 93.0 milliwatts  |  |
| Operating Tempurature Range:   |  |
| 55.0/+125.0 degrees celsius  |  |
| storage Tempurature Range:   |  |
| 65.0/+150.0 degrees celsius  |  |
| eatures Provided:  |  |
| Ionolithic and schottky  |  |
| nclosure Material:   |  |
| Ceramic  |  |
| nclosure Configuration:  |  |
| lat pack   |  |
| Dutput Logic Form:   |  |
| ransistor-transistor logic   |  |
| nput Circuit Pattern:  |  |
| input  |  |
| Design Function And Quantity:  |  |
| encoder, priority  |  |
| Current Rating Per Characteristic:                                   |  |
| 5.00 milliamperes reverse current, dc absolute                       |  |
| erminal Surface Treatment:   |  |
| Solder   |  |
| oltage Rating And Type Per Characteristic:                           |  |
| .0 volts power source  |  |
| est Data Document:   |  |
| 6906-mil-std-883 standard (includes industry or association standard | ls, individual manufactureer standards, etc.). |
| erminal Type And Quantity:   |  |
| 6 flat leads   |  |
| Shelf Life:  |  |
| I/a  |  |
| Init Of Measure:   |  |
|  |  |
| Demilitarization:  |  |
| 'es - demil/mli  |  |
| iig:   |  |
| 458a0  |  |