

View Online at <https://aerobasegroup.com/nsn/5962-01-279-0149>

Body Length:

Between 0.442 inches and 0.458 inches

Body Width:

Between 0.442 inches and 0.458 inches

Body Height:

Between 0.064 inches and 0.100 inches

Maximum Power Dissipation Rating:

1.2 watts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Programmable and monolithic and bipolar

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

20 input

Case Outline Source And Designator:

C-4 mil-m-38510

Current Rating Per Characteristic:

100.00 milliamperes forward current, nonrepetitive, peak total value

Terminal Surface Treatment:

Solder

Product Name:

20-input 8-output and-or invert gate array

Voltage Rating And Type Per Characteristic:

12.0 volts power source

Time Rating Per Characteristic:

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

Memory Device Type:

Pal

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0