

View Online at <https://aerobasegroup.com/nsn/5962-01-279-0150>

**Body Length:**

Between 0.442 inches and 0.458 inches

**Body Width:**

Between 0.442 inches and 0.458 inches

**Body Height:**

Between 0.064 inches and 0.100 inches

**Maximum Power Dissipation Rating:**

1.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Programmable and monolithic and bipolar

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Leadless flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

20 input

**Case Outline Source And Designator:**

C-4 mil-m-38510

**Current Rating Per Characteristic:**

100.00 milliamperes forward current, nonrepetitive, peak total value

**Terminal Surface Treatment:**

Solder

**Product Name:**

20-input 6-output registered and-or gate array

**Voltage Rating And Type Per Characteristic:**

12.0 volts power source

**Time Rating Per Characteristic:**

35.00 nanoseconds propagation delay time, low to high level output and 35.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Pal

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

28 leadless

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A458a0