## NSN 5962-01-283-4323

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-283-4323

Body Length:
Between 0.342 inches and 0.358 inches
Body Width:
Between 0.342 inches and 0.358 inches
Body Height:
Between 0.064 inches and 0.100 inches
Maximum Power Dissipation Rating:
220.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Schottky and w/odd-even check and monolithic and hermetically sealed
Inclosure Material:
Ceramic
Inclosure Configuration:
Leadless flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
9 input
Design Function And Quantity:
1 generator, parity, checker
Case Outline Source And Designator:
C-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
20 leadless
Specification Data:
81349-mil-m-38510/349 government specification
Shelf Life:
N/a

Yes - demil/mli

**Unit Of Measure:** 

Demilitarization:

## NSN 5962-01-283-4323

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0