

View Online at <https://aerobasegroup.com/nsn/5962-01-283-4462>

Body Length:

0.440 inches

Body Width:

Between 0.245 inches and 0.285 inches

Body Height:

Between 0.045 inches and 0.085 inches

Maximum Power Dissipation Rating:

750.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

An/ssn- (v) precise integrated navigation system; aircraft, galaxy c-5; forrestal class cv; avenger class mcm; support equipment, c-130 aircraft; aircraft, starlifter c-141

Features Provided:

W/enable and hermetically sealed and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Flat pack

Input Circuit Pattern:

4 channel

Design Function And Quantity:

1 multiplexer, analog

Case Outline Source And Designator:

F-5 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

44.0 volts power source

Time Rating Per Characteristic:

1500.00 nanoseconds propagation delay time, low to high level output and 1000.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 flat leads

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0