NSN 5962-01-283-8230

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-283-8230 **Body Length:** 0.350 inches **Body Width:** 0.350 inches **Body Height:** 0.100 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and high speed and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Leadless flat pack **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 3 input **Design Function And Quantity:** 1 decoder, three to eight line **Case Outline Source And Designator:** C-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Test Data Document:** 81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Terminal Type And Quantity:** 20 leadless **Specification Data:** 81349-mil-m-38510/658 government specification Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-01-283-8230

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0