NSN 5962-01-284-1764

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-284-1764

Demi	litarization:
	Of Measure:
N/a	
	inted circuit
	inal Type And Quantity:
	6-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
	Data Document:
outpu	
	10 nanoseconds propagation delay time, low to high level output and 140.00 nanoseconds propagation delay time, high to low level
	Rating Per Chacteristic:
	volts power source
	ge Rating And Type Per Characteristic:
Solde	
	inal Surface Treatment:
1 driv	er
Desiç	gn Function And Quantity:
8 inpu	ut
Input	Circuit Pattern:
Dual-	in-line
Inclo	sure Configuration:
Cerar	mic
Inclo	sure Material:
Herm	etically sealed and burn in and w/inhibit and w/resistor and electrostatic sensitive
Featu	ures Provided:
-65.0/	/+150.0 degrees celsius
Stora	age Tempurature Range:
-55.0/	/+125.0 degrees celsius
Opera	ating Tempurature Range:
2.0 w	atts
Махії	mum Power Dissipation Rating:
0.185	b inches
Body	/ Height:
0.310) inches
Body	/ Width:
0.840) inches

Yes - demil/mli

Fiig:

A458a0