## NSN 5962-01-284-1765

Hybrid Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-284-1765 **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 200.0 milliwatts **Operating Tempurature Range:** +0.0/+70.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and hermetically sealed and burn in and optically coupled and hybrid and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Design Function And Quantity:** 1 isolator, optical **Case Outline Source And Designator:** D-2 mil-m-38510 **Current Rating Per Characteristic:** 4.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 20.0 volts power source **Time Rating Per Chacteristic:** 100.00 microseconds delay **Hybrid Technology Type:** Monolithic **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 16 printed circuit Shelf Life: N/a **Unit Of Measure:** 

Demilitarization:

Yes - demil/mli

## NSN 5962-01-284-1765

Hybrid Microcircuit - Page 2 of 2



Fiig:

A458a0