

View Online at <https://aerobasegroup.com/nsn/5962-01-285-2458>

Body Length:

Between 0.342 inches and 0.358 inches

Body Width:

Between 0.342 inches and 0.358 inches

Body Height:

Between 0.064 inches and 0.100 inches

Maximum Power Dissipation Rating:

187.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and schottky and monolithic

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

6 input

Design Function And Quantity:

4 generator, baud rate

Case Outline Source And Designator:

C-2 mil-m-38510

Terminal Surface Treatment:

Gold

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Precious Material And Location:

Terminal surfaces gold

Precious Material:

Gold

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 leadless

Specification Data:

81349-mil-m-38510/341 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0