Digital-linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-285-3503

Body Length:

1.310 inches

Body Width:

0.800 inches

Body Height:

0.168 inches

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

5865-01-138-0075

Features Provided:

Hermetically sealed and burn in and bipolar and hybrid

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

5 input

Design Function And Quantity:

1 converter, analog to digital

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-18.0 volts power source and 18.0 volts power source

Time Rating Per Chacteristic:

700.00 nanoseconds propagation delay time, low to high level output and 700.00 nanoseconds propagation delay time, high to low level output

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

24 printed circuit

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0