NSN 5962-01-286-2241

Linear Microcircuit - Page 1 of 1

Fiig: A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-286-2241 **Body Length:** 0.405 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 830.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Burn in and hermetically sealed and low power and monolithic and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 2 input **Design Function And Quantity:** 2 amplifier, operational, general purpose **Case Outline Source And Designator:** D-4 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 32.0 volts power source **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 8 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli