

View Online at <https://aerobasegroup.com/nsn/5962-01-286-2246>

**Body Length:**

0.390 inches

**Body Width:**

Between 0.235 inches and 0.260 inches

**Body Height:**

Between 0.045 inches and 0.085 inches

**Maximum Power Dissipation Rating:**

115.5 milliwatts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Hermetically sealed and burn in and schottky and w/schmitt trigger

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Flat pack

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

Hex 1 input

**Design Function And Quantity:**

6 inverter

**Case Outline Source And Designator:**

F-2 mil-m-38510

**Terminal Surface Treatment:**

Solder

**Voltage Rating And Type Per Characteristic:**

-0.5 volts power source and 7.0 volts power source

**Time Rating Per Characteristic:**

52.00 nanoseconds propagation delay time, low to high level output and 52.00 nanoseconds propagation delay time, high to low level output

**Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

14 flat leads

**Specification Data:**

81349-mil-m-38510/313 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

**Demilitarization:**

Yes - demil/mli

**Fig:**

A458a0