

View Online at <https://aerobasegroup.com/nsn/5962-01-286-3678>

Body Length:

0.840 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

137.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

End Application:

Support equipment, b-52 aircraft; comuncations systems an/wsc-3; support equipment, b-1 aircraft; radar set, lightweight 3d (an/tps-59); countermeasure set, an/slq-32; radar set, firefinder (an/tpq-36); radar, series an/sps-49 (v); radar threat emitter an/mst-t1; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); missile, tomahawk

Features Provided:

Schottky and monolithic and edge triggered and w/clear and w/clock and w/preset

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 5 input

Criticality Code Justification:

Feat

Design Function And Quantity:

2 flip-flop, j-k

Case Outline Source And Designator:

D-2 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Characteristic:

11.00 nanoseconds propagation delay time, low to high level output and 11.00 nanoseconds propagation delay time, high to low level output

Special Features:

Weapon system essential

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Specification Data:

81349-mil-m-38510/71 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A458a0