NSN 5962-01-286-3678

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-286-3678

Body Length:

0.840 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

0.185 inches

Maximum Power Dissipation Rating:

137.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

End Application:

Support equipment, b-52 aircraft; comunications systems an/wsc-3; support equipment, b-1 aircraft; radar set, lightweight 3d (an/tps-59); countermeasure set, an/slq-32; radar set, firefinder (an/tpq-36); radar, series an/sps-49 (v); radar threat emiter an/mst-t1; aircraft, (ac-130h, mc-130h, ec-130e, hc-130); missile, tomahawk

Features Provided:

Schottky and monolithic and edge triggered and w/clear and w/clock and w/preset

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Dual 5 input

Criticality Code Justification:

Feat

Design Function And Quantity:

2 flip-flop, j-k

Case Outline Source And Designator:

D-2 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Time Rating Per Chacteristic:

11.00 nanoseconds propagation delay time, low to high level output and 11.00 nanoseconds propagation delay time, high to low level output

Special Features:

Weapon system essential

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

NSN 5962-01-286-3678

Digital Microcircuit - Page 2 of 2



	Spe	cific	ation	Data
--	-----	-------	-------	------

81349-mil-m-38510/71 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0