NSN 5962-01-287-1508

/ Microcircuit - Page 1 of 1



group.com/nsn/5962-01-287-1508

| Memory Microcircuit - Page 1 of 1 |
|---|
| View Online at https://aerobasegroup.com/nsn/5962-01-2 |
| Body Length: |
| 0.450 inches |
| Body Width: |
| 0.450 inches |
| Body Height: |
| 0.100 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Monolithic and programmable and electrostatic sensitive |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Leadless flat pack |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 14 input |
| Case Outline Source And Designator: |
| |

C-4 mil-m-38510

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-0.5 volts power source and 7.0 volts power source

Memory Device Type:

Rom

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 leadless

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0