NSN 5962-01-287-2395

Digital Microcircuit - Page 1 of 1



| view Online at https://aerobasegroup.com/nsn/5962-01-287-2595 |
|--|
| Body Length: |
| Between 0.342 inches and 0.358 inches |
| Body Width: |
| Between 0.342 inches and 0.358 inches |
| Body Height: |
| Between 0.064 inches and 0.100 inches |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Hermetically sealed and burn in and electrostatic sensitive and w/clock and w/enable |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Leadless flat pack |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 18 input |
| Design Function And Quantity: |
| 8 flip-flop, d-type, clocked |
| Case Outline Source And Designator: |
| C-2 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| -0.5 volts power source and 7.0 volts power source |
| Time Rating Per Chacteristic: |
| 15.00 nanoseconds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 20 leadless |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

Yes - demil/mli

Fiig:

A458a0