## NSN 5962-01-287-8529



Memory Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-287-8529 **Body Length:** Between 1.435 inches and 1.485 inches **Body Width:** Between 0.515 inches and 0.599 inches **Body Height:** Between 0.140 inches and 0.180 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **End Application:** 7010-01-211-9822 **Features Provided:** Hermetically sealed and programmable and ultraviolet erasable and w/enable and bidirectional and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 25 input **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.6 volts power source and 7.0 volts power source **Time Rating Per Chacteristic:** 

250.00 nanoseconds propagation delay time, low to high level output and 250.00 nanoseconds propagation delay time, high to low level output

#### **Memory Device Type:**

Rom

## **Memory Capacity:**

Unknown

### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

## **Terminal Type And Quantity:**

28 printed circuit

#### Shelf Life:

N/a

## **Unit Of Measure:**

#### **Demilitarization:**

Yes - demil/mli

# NSN 5962-01-287-8529

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0