NSN 5962-01-289-1219

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-289-1219

Overall Height: 0.400 inches **Body Length:** 0.840 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.180 inches **Maximum Power Dissipation Rating:** 100.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** Nuclear reactor boundry area; seawolf class ssn; nuclear power plants **Features Provided:** Monolithic and positive outputs **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 7 input **Criticality Code Justification: Design Function And Quantity:** 1 decoder, binary coded decimal to seven segment **Case Outline Source And Designator:** D-2 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 20.0 volts power source **Special Features:** Item must comply with requirements of desc production standard no. L04039; for navy nuclear propulsion plant products only; weapon system essential

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

16 printed circuit

NSN 5962-01-289-1219

Digital Microcircuit - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A458a0