NSN 5962-01-289-4264

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-289-4264

view Offilite at https://defobasegroup.com/his//0302-01-203-4204
Overall Length:
0.785 inches
Overall Height:
0.400 inches
Overall Width:
0.320 inches
Body Length:
0.785 inches
Body Width:
0.310 inches
Body Height:
0.140 inches
Maximum Power Dissipation Rating:
400.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Internally compensated and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 amplifier, operational, general purpose
Case Outline Source And Designator:
D-1 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
22.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 printed circuit
Specification Data:

N/a

Shelf Life:

81349-mil-m-38510/101 government specification

NSN 5962-01-289-4264

Linear Microcircuit - Page 2 of 2



	Of			

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0