NSN 5962-01-290-1585

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-290-1585 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.130 inches and 0.185 inches **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Electrostatic sensitive and programmed and w/clock and w/enable and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 16 input **Case Outline Source And Designator:** D-8 mil-m-38510 **Current Rating Per Characteristic:** 50.00 milliamperes reverse current, dc absolute **Terminal Surface Treatment:** Solder **Product Name:** Registered and-or gate array **Voltage Rating And Type Per Characteristic:** -0.5 volts power source and 12.0 volts power source **Time Rating Per Chacteristic:** 75.00 nanoseconds propagation delay time, high to low level output and 75.00 nanoseconds propagation delay time, low to high level output **Memory Device Type: Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a

Demilitarization:

Unit Of Measure:

Yes - demil/mli

NSN 5962-01-290-1585

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0