NSN 5962-01-290-1586

Memory Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-290-1586 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.130 inches and 0.185 inches **Maximum Power Dissipation Rating:** 300.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Bidirectional and bipolar and programmable and w/enable and w/disable and w/clock **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** 16 input **Case Outline Source And Designator:** D-8 mil-m-38510 **Terminal Surface Treatment:** Solder **Product Name:** Registered and-or gate array Voltage Rating And Type Per Characteristic: -0.5 volts power source and 12.0 volts power source **Memory Device Type:** Pal **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 20 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:** Yes - demil/mli

Fiig:

A458a0