NSN 5962-01-290-2309

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-290-2309

Overall Length:
1.490 inches
Overall Height:
0.432 inches
Body Length:
1.490 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
Between 0.172 inches and 0.217 inches
Maximum Power Dissipation Rating:
170.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and ultraviolet erasable and programmed and w/enable
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Dual-in-line Output Logic Form:
Output Logic Form:
Output Logic Form: Complementary-metal oxide-semiconductor logic
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern:
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator:
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic:
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic: 10.00 milliamperes supply
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic: 10.00 milliamperes supply Terminal Surface Treatment:
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic: 10.00 milliamperes supply Terminal Surface Treatment: Solder
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic: 10.00 milliamperes supply Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic:
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic: 10.00 milliamperes supply Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -2.0 volts power source and 7.0 volts power source
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic: 10.00 milliamperes supply Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -2.0 volts power source and 7.0 volts power source Capitance Rating Per Characteristic:
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic: 10.00 milliamperes supply Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -2.0 volts power source and 7.0 volts power source Capitance Rating Per Characteristic: 10.00 input picofarads and 12.00 output picofarads
Output Logic Form: Complementary-metal oxide-semiconductor logic Input Circuit Pattern: 16 input Case Outline Source And Designator: D-10 mil-m-38510 Current Rating Per Characteristic: 10.00 milliamperes supply Terminal Surface Treatment: Solder Voltage Rating And Type Per Characteristic: -2.0 volts power source and 7.0 volts power source Capitance Rating Per Characteristic: 10.00 input picofarads and 12.00 output picofarads Time Rating Per Chacteristic:

Unknown

Memory Capacity:

NSN 5962-01-290-2309

Memory Microcircuit - Page 2 of 2



1	Toet	Data	Do	CII	me	'n	+
ı	ı est	vala	υu	Gu	HILL	2 I I	L

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

Unit Of Measure:

--

N/a

Demilitarization:

Yes - demil/mli

Fiig:

A458a0