

View Online at <https://aerobasegroup.com/nsn/5962-01-290-8812>

Overall Length:

1.060 inches

Overall Height:

0.400 inches

Body Length:

1.060 inches

Body Width:

Between 0.220 inches and 0.310 inches

Body Height:

Between 0.130 inches and 0.185 inches

Maximum Power Dissipation Rating:

170.0 milliwatts

Operating Temperature Range:

-55.0/+125.0 degrees celsius

Storage Temperature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Ultraviolet erasable and monolithic and programmed and w/enable and w/disable

Inclosure Material:

Ceramic

Inclosure Configuration:

Dual-in-line

Output Logic Form:

Complementary-metal oxide-semiconductor logic

Input Circuit Pattern:

16 input

Case Outline Source And Designator:

D-8 mil-m-38510

Current Rating Per Characteristic:

140.00 microamperes reverse current, dc blank

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

-2.0 volts input and 7.0 volts input

Capitance Rating Per Characteristic:

10.00 input picofarads and 12.00 output picofarads

Time Rating Per Characteristic:

200.00 nanoseconds af output megawatts

Test Data Document:

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

Terminal Type And Quantity:

28 printed circuit

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0