## NSN 5962-01-290-9534

Memory Microcircuit - Page 1 of 1

**Fiig:** A458a0



View Online at https://aerobasegroup.com/nsn/5962-01-290-9534

Body Length:
1.290 inches
Body Width:
Between 0.500 inches and 0.610 inches
Body Height:
0.210 inches
Operating Tempurature Range:
-55.0/+100.0 degrees celsius
Storage Tempurature Range:
-65.0/+125.0 degrees celsius
Features Provided:
Programmable and erasable and electrostatic sensitive and hermetically sealed
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
13 input
Case Outline Source And Designator:
D-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
26.5 volts power source
Time Rating Per Chacteristic:
450.00 nanoseconds propagation delay time, low to high level output and 450.00 nanoseconds propagation delay time, high to low level
output
Memory Device Type:
Rom
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli