NSN 5962-01-291-0880

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-291-0880

view Offilite at https://aerobasegroup.com/nsi//0302-01-231-0000
Overall Length:
0.280 inches
Overall Height:
0.070 inches
Overall Width:
0.590 inches
Body Length:
0.280 inches
Body Width:
0.200 inches
Body Height:
0.070 inches
Maximum Power Dissipation Rating:
350.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Internally compensated and monolithic
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Input Circuit Pattern:
Dual 2 input
Design Function And Quantity:
2 amplifier, operational, general purpose
Case Outline Source And Designator:
F-3 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
22.0 volts power source
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
14 flat leads
Specification Data:

N/a

Shelf Life:

81349-mil-m-38510/101 government specification

NSN 5962-01-291-0880

Linear Microcircuit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0