NSN 5962-01-291-2658



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-291-2658 **Body Length:** 1.060 inches **Body Width:** Between 0.220 inches and 0.310 inches **Body Height:** Between 0.140 inches and 0.185 inches **Maximum Power Dissipation Rating:** 2.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **End Application:** F-15 acft **Features Provided:** Hermetically sealed and burn in and programmed and monolithic and electrostatic sensitive **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 14 input **Criticality Code Justification:** Cbbl **Design Function And Quantity:** 1 gate, array **Case Outline Source And Designator:** D-8 mil-m-38510 **Time Rating Per Chacteristic:** 30.00 nanoseconds propagation delay time, low to high level output and 30.00 nanoseconds propagation delay time, high to low level output **Special Features: ALTE-RE-DIT-EMNS Test Data Document:** 07187-8511844-100 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

NSN 5962-01-291-2658

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0