NSN 5962-01-291-5016

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-291-5016

| View Online at https://aerobasegroup.com/nsn/5962-01-291-5016 |
|--|
| Body Length: |
| Between 0.640 inches and 0.662 inches |
| Body Width: |
| Between 0.640 inches and 0.662 inches |
| Body Height: |
| Between 0.064 inches and 0.120 inches |
| Maximum Power Dissipation Rating: |
| 1.0 watts |
| Operating Tempurature Range: |
| -55.0/+125.0 degrees celsius |
| Storage Tempurature Range: |
| -65.0/+150.0 degrees celsius |
| Features Provided: |
| Electrostatic sensitive and hermetically sealed and burn in and programmable and asynchronous |
| Inclosure Material: |
| Ceramic |
| Inclosure Configuration: |
| Leadless flat pack |
| Output Logic Form: |
| Complementary-metal oxide-semiconductor logic |
| Input Circuit Pattern: |
| 26 input |
| Design Function And Quantity: |
| 1 control, interface |
| Case Outline Source And Designator: |
| C-5 mil-m-38510 |
| Terminal Surface Treatment: |
| Solder |
| Voltage Rating And Type Per Characteristic: |
| 5.5 volts power source |
| Time Rating Per Chacteristic: |
| 120.00 nanoseconds propagation delay time, low to high level output and 120.00 nanoseconds propagation delay time, high to low level |
| output |
| Test Data Document: |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity: |
| 44 leadless |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

Demilitarization:

Yes - demil/mli

NSN 5962-01-291-5016

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0