## NSN 5962-01-291-7754

Linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-291-7754

| Overall Length:  |
|--|
| 0.960 inches   |
| Overall Height:  |
| 0.400 inches   |
| Overall Width:   |
| 0.320 inches   |
| Body Length:   |
| 0.960 inches   |
| Body Width:  |
| 0.310 inches   |
| Body Height:   |
| 0.130 inches   |
| Maximum Power Dissipation Rating:  |
| 1.1 milliwatts   |
| Operating Tempurature Range:   |
| -55.0/+125.0 degrees celsius   |
| Storage Tempurature Range:   |
| -65.0/+150.0 degrees celsius   |
| Features Provided:   |
| High current and monolithic  |
| Inclosure Material:  |
| Ceramic  |
| Inclosure Configuration:   |
| Dual-in-line   |
| Design Function And Quantity:  |
| 1 driver, high current   |
| Case Outline Source And Designator:  |
| D-6 mil-m-38510  |
| Current Rating Per Characteristic:   |
| 500.00 milliamperes forward current, dc any acceptable   |
| Terminal Surface Treatment:  |
| Solder   |
| Voltage Rating And Type Per Characteristic:  |
| 50.0 volts power source  |
| Test Data Document:  |
| 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Type And Quantity:  |
| 18 printed circuit   |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
| <u></u>  |

## NSN 5962-01-291-7754

Linear Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0