NSN 5962-01-292-2396

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-292-2396 **Body Length:** 1.490 inches **Body Width:** Between 0.500 inches and 0.610 inches **Body Height:** Between 0.165 inches and 0.210 inches **Maximum Power Dissipation Rating:** 1.0 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and ultraviolet erasable and monolithic and w/enable **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 17 input **Case Outline Source And Designator:** D-10 mil-m-38510 **Current Rating Per Characteristic:** 140.00 milliamperes supply **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 6.5 volts total supply **Memory Device Type:** Prom **Memory Capacity:** Unknown **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life:

--

N/a

Unit Of Measure:

NSN 5962-01-292-2396

Memory Microcircuit - Page 2 of 2



Demilitarization:

No

Fiig:

A458a0