NSN 5962-01-292-3530

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-292-3530

Body Length:
Between 1.185 inches and 1.222 inches
Body Width:
Between 0.375 inches and 0.395 inches
Body Height:
Between 0.150 inches and 0.175 inches
Operating Tempurature Range:
+0.0/+85.0 degrees celsius
Storage Tempurature Range:
65.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and positive outputs
nclosure Material:
Ceramic
nclosure Configuration:
Dual-in-line
Output Logic Form:
Transistor-transistor logic
nput Circuit Pattern:
Hex 2 input
Design Function And Quantity:
6 translator, ecl to ttl
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
4.00 nanoseconds propagation delay time, low to high level output and 4.00 nanoseconds propagation delay time, high to low level output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
24 printed circuit
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
Yes - demil/mli
Fiig:
A458a0