NSN 5962-01-292-8853

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-292-8853 **Body Length:** 0.750 inches **Body Width:** 0.250 inches **Maximum Power Dissipation Rating:** 49.5 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Monolithic and schottky and electrostatic sensitive and bipolar **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** Hex 1 input **Design Function And Quantity:** 1 gate, nand **Terminal Surface Treatment:** Solder **Product Name:** Microcircuits, digital, bipolar, schottky ttl, nand gates, monolithic silicon/generic p/n 54s04 Voltage Rating And Type Per Characteristic: -0.5 volts input and 7.0 volts input **Nuclear Hardness Critical Feature:** Hardened

Test Data Document:

 $96906 \hbox{-mil-std-}883 \ standard \ (includes \ industry \ or \ association \ standards, \ individual \ manufactureer \ standards, \ etc.).$

Terminal Type And Quantity:

14 printed circuit

.

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

Yes - demil/mli

Fiig:

A458a0