## NSN 5962-01-292-9212

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-292-9212 **Body Length:** 1.895 inches **Body Width:** 0.775 inches **Body Height:** 0.180 inches **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius **Storage Tempurature Range:** -65.0 to 150.0 degrees celsius **Features Provided:** Electrostatic sensitive and hybrid and hermetically sealed **Inclosure Material:** Metal **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** 25 input **Design Function And Quantity:** 1 converter, digital to resolver and 1 converter, digital to synchro **Terminal Surface Treatment:** Gold **Voltage Rating And Type Per Characteristic:** 18.0 volts power source **Time Rating Per Chacteristic:** 200.00 nanoseconds propagation delay time, low to high level output and 200.00 nanoseconds propagation delay time, high to low level output **Precious Material And Location:** Terminal surfaces gold **Precious Material:** Gold **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 36 printed circuit Shelf Life: N/a

**Demilitarization:** Yes - demil/mli

**Unit Of Measure:** 

## NSN 5962-01-292-9212

Digital-linear Microcircuit - Page 2 of 2



Fiig:

A458a0