NSN 5962-01-293-6611

Digital-linear Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-293-6611 **Body Length:** 1.475 inches **Body Width:** 0.775 inches **Body Height:** 0.175 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -55.0 to 125.0 degrees celsius Storage Tempurature Range: -65.0 to 150.0 degrees celsius **End Application:** 1005-01-177-9237 **Features Provided:** Hermetically sealed and burn in and hybrid and bipolar **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** Transistor-transistor logic **Input Circuit Pattern:** 23 input **Design Function And Quantity:** 1 converter, digital to analog **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 15.0 volts power source **Time Rating Per Chacteristic:** 500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 28 printed circuit Shelf Life: N/a

Demilitarization: Yes - demil/mli

Unit Of Measure:

NSN 5962-01-293-6611

Digital-linear Microcircuit - Page 2 of 2



Fiig:

A458a0