NSN 5962-01-293-7711

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-293-7711 **Body Length:** Between 0.745 inches and 0.770 inches **Body Width:** Between 0.240 inches and 0.260 inches **Body Height:** Between 0.105 inches and 0.180 inches **Maximum Power Dissipation Rating:** 500.0 milliwatts **Operating Tempurature Range:** -40.0/+85.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** W/resistor and burn in and positive outputs **Inclosure Material: Plastic Inclosure Configuration:** Dual-in-line **Output Logic Form:** Complementary-metal oxide-semiconductor logic **Input Circuit Pattern:** Hex 1 input **Design Function And Quantity:** 6 schmitt trigger **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: -0.5 volts power source and 20.0 volts power source **Time Rating Per Chacteristic:** 280.00 nanoseconds propagation delay time, low to high level output and 280.00 nanoseconds propagation delay time, high to low level output **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Yes - demil/mli

Fiig:

A458a0