NSN 5962-01-294-3247



Digital Microcircuit - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5962-01-294-3247 **Body Length:** 2.096 inches **Body Width:** Between 0.510 inches and 0.620 inches **Body Height:** Between 0.165 inches and 0.210 inches **Maximum Power Dissipation Rating:** 1.5 watts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius Storage Tempurature Range: -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and monolithic and w/clock and bidirectional **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Output Logic Form:** N-type metal oxide-semiconductor logic **Input Circuit Pattern:** 28 input **Design Function And Quantity:** 1 control, memory access **Case Outline Source And Designator:** D-5 mil-m-38510 **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 7.0 volts power source **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 40 printed circuit Shelf Life:

Demilitarization: Yes - demil/mli

Unit Of Measure:

N/a

NSN 5962-01-294-3247

Digital Microcircuit - Page 2 of 2



Fiig:

A458a0