NSN 5962-01-294-4750

Digital Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-294-4750

Body Le	- 44
DOOV I E	nam

Between 0.342 inches and 0.358 inches

Body Width:

Between 0.342 inches and 0.358 inches

Body Height:

Between 0.060 inches and 0.100 inches

Maximum Power Dissipation Rating:

22.0 milliwatts

Operating Tempurature Range:

-55.0/+125.0 degrees celsius

Storage Tempurature Range:

-65.0/+150.0 degrees celsius

Features Provided:

Hermetically sealed and burn in and bipolar and low power and schottky

Inclosure Material:

Ceramic

Inclosure Configuration:

Leadless flat pack

Output Logic Form:

Transistor-transistor logic

Input Circuit Pattern:

Quad 2 input

Design Function And Quantity:

4 gate, and

Case Outline Source And Designator:

C-2 mil-m-38510

Current Rating Per Characteristic:

2.40 milliamperes reverse current, dc absolute

Terminal Surface Treatment:

Solder

Voltage Rating And Type Per Characteristic:

7.0 volts power source

Test Data Document:

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

20 leadless

Specification Data:

81349-mil-m-38510/374 government specification

Shelf Life:

N/a

Unit Of Measure:

-

NSN 5962-01-294-4750

Digital Microcircuit - Page 2 of 2



_		••	• •				
וו	em	ш	112	rız	211	n	٠.

No

Fiig:

A458a0