NSN 5962-01-294-4754

Memory Microcircuit - Page 1 of 2

Demilitarization: Yes - demil/mli



View Online at https://aerobasegroup.com/nsn/5962-01-294-4754

Body Length:
0.640 inches
Body Width:
Between 0.300 inches and 0.420 inches
Body Height:
Between 0.045 inches and 0.090 inches
Maximum Power Dissipation Rating:
935.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+165.0 degrees celsius
Features Provided:
Schottky and monolithic and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Flat pack
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
16 input
Case Outline Source And Designator:
F-6 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Memory Device Type:
Ram
Test Data Document:
81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
22 flat leads
Specification Data:
81349-mil-m-38510/231 government specification
Shelf Life:
N/a
Unit Of Measure:

NSN 5962-01-294-4754

Memory Microcircuit - Page 2 of 2



Fiig:

A458a0