## NSN 5962-01-294-5804

Linear Microcircuit - Page 1 of 1



low to high level output and 500.00 nanoseconds propagation delay time, high to low level

View Online at https://aerobasegroup.com/nsn/5962-01-294-5804

Body Length:
0.840 inches
Body Width:
Between 0.220 inches and 0.310 inches
Body Height:
Between 0.140 inches and 0.185 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-55.0/+150.0 degrees celsius
Features Provided:
Hermetically sealed and burn in and monolithic and positive outputs
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Input Circuit Pattern:
Hex 1 input
Design Function And Quantity:
6 receiver
Case Outline Source And Designator:
D-2 mil-m-38510
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
500.00 nanoseconds propagation delay time, low to high level output and 500.00 nanoseconds propagation delay
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
16 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A458a0