## NSN 5962-01-294-6729

Digital Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-294-6729

Body Length:
Between 0.898 inches and 1.200 inches
Body Width:
Between 0.216 inches and 0.334 inches
Body Height:
Between 0.078 inches and 0.250 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Schottky and programmable and 3-state output and bipolar
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line Dual-in-line
Output Logic Form:
Transistor-transistor logic
Input Circuit Pattern:
16 input
Design Function And Quantity:
4 gate, array
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
7.0 volts power source
Time Rating Per Chacteristic:
45.00 nanoseconds propagation delay time, low to high level output and 45.00 nanoseconds propagation delay time, high to low level
output
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
20 printed circuit
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A458a0