# NSN 5962-01-294-7685

Linear Microcircuit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5962-01-294-7685

# Body Length: 0.405 inches Body Width: Between 0.220 inches and 0.310 inches Body Height: Between 0.140 inches and 0.185 inches Maximum Power Dissipation Rating: 400.0 milliwatts

**Operating Tempurature Range:** 

-55.0/+125.0 degrees celsius

## Storage Tempurature Range:

-65.0/+150.0 degrees celsius

**End Application:** 

6625-01-021-6383

Features Provided:

Hermetically sealed and burn in and monolithic and wideband

Inclosure Material:

Ceramic

**Inclosure Configuration:** 

Dual-in-line

Input Circuit Pattern:

2 input

Design Function And Quantity:

1 amplifier, operational, general purpose

Case Outline Source And Designator:

D-4 mil-m-38510

**Terminal Surface Treatment:** 

Solder

#### Time Rating Per Chacteristic:

1500.00 nanoseconds propagation delay time, low to high level output and 1500.00 nanoseconds propagation delay time, high to low level output

#### **Test Data Document:**

81349-mil-m-38510 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

### **Specification Data:**

81349-mil-m-38510/114 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig: