NSN 5962-01-294-9786

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-294-9786

| Body Length | · |
|-----------------|---|
| 0.840 inches | • |
| Body Width: | |
| | 20 inches and 0.310 inches |
| Body Height | |
| | • I0 inches and 0.185 inches |
| | ower Dissipation Rating: |
| 827.0 milliwat | |
| | empurature Range: |
| | degrees celsius |
| | auguste constant purature Range: |
| | degrees celsius |
| Features Pro | - |
| | sealed and burn in and monolithic and positive outputs |
| Inclosure Ma | |
| Ceramic | |
| Inclosure Co | nfiguration: |
| Dual-in-line | |
| Output Logic | c Form: |
| Emitter-coupl | |
| Input Circuit | |
| 10 input | |
| Case Outline | e Source And Designator: |
| D-2 mil-m-38 | |
| Terminal Su | rface Treatment: |
| Solder | |
| Voltage Rati | ng And Type Per Characteristic: |
| -8.0 volts pov | wer source |
| Time Rating | Per Chacteristic: |
| 15.00 nanose | econds propagation delay time, low to high level output and 15.00 nanoseconds propagation delay time, high to low level |
| output | |
| Memory Dev | ісе Туре: |
| Ram | |
| Memory Cap | acity: |
| Unknown | |
| Test Data Do | ocument: |
| 96906-mil-sto | I-883 standard (includes industry or association standards, individual manufactureer standards, etc.). |
| Terminal Typ | be And Quantity: |
| 16 printed cire | cuit |
| Shelf Life: | |
| N/a | |
| Unit Of Meas | sure: |

--

NSN 5962-01-294-9786

Memory Microcircuit - Page 2 of 2

Demilitarization:

Yes - demil/mli

Fiig:

A458a0

