## NSN 5962-01-295-2339

Digital Microcircuit - Page 1 of 2

20 flat leads



View Online at https://aerobasegroup.com/nsn/5962-01-295-2339

Overall Length:
0.358 inches
Overall Height:
0.100 inches
Overall Width:
0.358 inches
Body Length:
0.358 inches
Body Width:
0.358 inches
Body Height:
0.100 inches
Maximum Power Dissipation Rating:
500.0 milliwatts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+150.0 degrees celsius
Features Provided:
Fast carry and monolithic and 3-state output
Inclosure Material:
Ceramic
Inclosure Configuration:
Leaded chip carrier
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
11 input
Design Function And Quantity:
8 latch, d
Case Outline Source And Designator:
C-2 mil-m-38510
Current Rating Per Characteristic:
100.00 milliamperes forward current, nonrepetitive, peak total value
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts total supply and 6.0 volts total supply
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.)
Terminal Type And Quantity:

## NSN 5962-01-295-2339

Digital Microcircuit - Page 2 of 2



_					
•	n	<b>0</b> 1	•	12	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

Yes - demil/mli

Fiig:

A458a0