NSN 5962-01-295-8584

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-295-8584

3· · · · · · · · · · · · · · · · · · ·
Body Length:
Between 1.380 inches and 1.420 inches
Body Width:
Between 0.584 inches and 0.604 inches
Body Height:
0.280 inches
Maximum Power Dissipation Rating:
4.0 watts
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Storage Tempurature Range:
-65.0/+155.0 degrees celsius
End Application:
5865-01-262-1191 data analysis c
Features Provided:
Hermetically sealed and burn in and electrostatic sensitive and w/enable and bidirectional
Inclosure Material:
Ceramic
Inclosure Configuration:
Dual-in-line
Output Logic Form:
Complementary-metal oxide-semiconductor logic
Input Circuit Pattern:
26 input
Terminal Surface Treatment:
Solder
Voltage Rating And Type Per Characteristic:
-0.5 volts power source and 7.0 volts power source
Time Rating Per Chacteristic:
100.00 nanoseconds propagation delay time, low to high level output and 100.00 nanoseconds propagation delay time, high to low level
output
Memory Device Type:
Ram
Memory Capacity:
Unknown
Test Data Document:
96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).
Terminal Type And Quantity:
28 printed circuit
Shelf Life:

--

N/a

Unit Of Measure:

NSN 5962-01-295-8584

Memory Microcircuit - Page 2 of 2



Demilitarization:

Yes - demil/mli

Fiig:

A458a0