

View Online at <https://aerobasegroup.com/nsn/5962-01-296-5444>

**Overall Height:**

Between 0.325 inches and 0.400 inches

**Body Length:**

1.280 inches

**Body Width:**

Between 0.220 inches and 0.310 inches

**Body Height:**

Between 0.140 inches and 0.185 inches

**Maximum Power Dissipation Rating:**

1.2 watts

**Operating Temperature Range:**

-55.0/+125.0 degrees celsius

**Storage Temperature Range:**

-65.0/+150.0 degrees celsius

**Features Provided:**

Bipolar and monolithic and programmable

**Inclosure Material:**

Ceramic

**Inclosure Configuration:**

Dual-in-line

**Output Logic Form:**

Transistor-transistor logic

**Input Circuit Pattern:**

20 input

**Case Outline Source And Designator:**

D-9 mil-m-38510

**Current Rating Per Characteristic:**

100.00 milliamperes forward current, nonrepetitive, peak total value

**Terminal Surface Treatment:**

Solder

**Product Name:**

20-input 4-output registered and-or gate array

**Voltage Rating And Type Per Characteristic:**

7.0 volts power source

**Time Rating Per Characteristic:**

50.00 nanoseconds propagation delay time, low to high level output and 50.00 nanoseconds propagation delay time, high to low level output

**Memory Device Type:**

Pal

**Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

**Terminal Type And Quantity:**

24 printed circuit

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fiig:**

A458a0