NSN 5962-01-297-0861



Linear Microcircuit - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5962-01-297-0861 **Body Length:** Between 0.755 inches and 0.785 inches **Body Width:** Between 0.245 inches and 0.280 inches **Body Height:** 0.180 inches **Maximum Power Dissipation Rating:** 600.0 milliwatts **Operating Tempurature Range:** -55.0/+125.0 degrees celsius **Storage Tempurature Range:** -65.0/+150.0 degrees celsius **Features Provided:** Hermetically sealed and burn in and monolithic **Inclosure Material:** Ceramic **Inclosure Configuration:** Dual-in-line **Input Circuit Pattern:** Dual 4 input **Design Function And Quantity:** 2 timer **Terminal Surface Treatment:** Solder Voltage Rating And Type Per Characteristic: 18.0 volts power source **Time Rating Per Chacteristic:** 300.00 nanoseconds propagation delay time, low to high level output and 300.00 nanoseconds propagation delay time, high to low level output **Test Data Document:** 96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.). **Terminal Type And Quantity:** 14 printed circuit Shelf Life: N/a **Unit Of Measure: Demilitarization:**

Yes - demil/mli

Fiig:

A458a0