## NSN 5962-01-298-4432

Memory Microcircuit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5962-01-298-4432

### Body Length: 1.290 inches

#### **Body Width:**

Between 0.500 inches and 0.610 inches

#### **Body Height:**

Between 0.150 inches and 0.210 inches

#### **Maximum Power Dissipation Rating:**

1.0 watts

#### **Operating Tempurature Range:**

-55.0/+125.0 degrees celsius

#### Storage Tempurature Range:

-55.0/+150.0 degrees celsius

#### **Features Provided:**

Hermetically sealed and burn in and monolithic and static operation and w/enable

#### Inclosure Material:

Ceramic

#### Inclosure Configuration:

Dual-in-line

#### **Output Logic Form:**

Complementary-metal oxide-semiconductor logic

#### Input Circuit Pattern:

22 input

#### **Case Outline Source And Designator:**

D-3 mil-m-38510

#### **Terminal Surface Treatment:**

Solder

#### Voltage Rating And Type Per Characteristic:

-0.3 volts power source and 7.0 volts power source

#### Time Rating Per Chacteristic:

55.00 nanoseconds propagation delay time, low to high level output and 55.00 nanoseconds propagation delay time, high to low level

### output

#### Memory Device Type:

Ram

#### **Memory Capacity:**

Unknown

#### **Test Data Document:**

96906-mil-std-883 standard (includes industry or association standards, individual manufactureer standards, etc.).

#### **Terminal Type And Quantity:**

24 printed circuit

#### Shelf Life:

N/a

#### Unit Of Measure:

# NSN 5962-01-298-4432

Memory Microcircuit - Page 2 of 2

#### Demilitarization:

Yes - demil/mli

Fiig:

A458a0

